

SCS Global Services does hereby certify that an independent assessment has been conducted on behalf of:

Jiangsu Zhengyoung Flooring Decoration Material Co., Ltd.

No.32, Cuibei Road, Henglin Town, Wujin District, Changzhou City, Jiangsu, China

For the following product(s):

See Addendum

The product(s) meet(s) all of the necessary qualifications to be certified for the following claim(s):

FloorScore®

Indoor Air Quality Certified to SCS-EC10.3-2014 v4.1

Conforms to the CDPH/EHLB Standard Method v1.2-2017 (California Section 01350), effective April 1, 2017, for the school classroom and private office parameters when modeled as Flooring.

Measured Concentration of Total Volatile Organic Compounds (TVOC): Less than/equal to 0.5 mg/m³ (in compliance with CDPH/EHLB Standard Method v1.2-2017)

Registration # SCS-FS-03713

Valid from: November 1, 2023 to October 31, 2024

SCS Global Services is currently the only certification body approved by the Resilient Floor Covering Institute (RFCI) to provide FloorScore® product certification; certified products are only listed on the SCS Green Products Guide, <http://www.scsglobalservices.com/certified-green-products-guide>.



A handwritten signature in black ink, reading "Stanley Mathuram".

Stanley Mathuram, PE, Executive Vice President
SCS Global Services
2000 Powell Street, Ste. 600, Emeryville, CA 94608 USA

Certification Addendum

Jiangsu Zhengyoung Flooring Decoration Material Co., Ltd.

Certification: Registration # SCS-FS-03713 | Valid from: November 1, 2023 to October 31, 2024

SCS Global Services is currently the only certification body approved by the Resilient Floor Covering Institute (RFCI) to provide FloorScore® product certification; certified products are only listed on the SCS Green Products Guide, <http://www.scsglobalservices.com/certified-green-products-guide>.

Addendum **FloorScore®**

Conformance: Indoor Air Quality Certified to SCS-EC10.3-2014 v4.1

Conforms to the CDPH/EHLB Standard Method v1.2-2017 (California Section 01350), effective April 1, 2017, for the school classroom and private office parameters when modeled as Flooring.

Measured Concentration of Total Volatile Organic Compounds (TVOC): Less than/equal to 0.5 mg/m³ (in compliance with CDPH/EHLB Standard Method v1.2-2017)

Products: **Vinyl Tile:**

PVC Flooring with Painting Bevel (*Maximum thickness: 6.0mm*), RIGID CORE Flooring with Painting Bevel (*Maximum thickness: 13.0mm*), Stone Plastic Composite (SPC) Flooring with Painting Bevel (*Maximum thickness: 8.0mm*), Vinyl Tile Flooring (*Maximum thickness: 5.0mm*), Wood Plastic Composite Flooring (*Maximum thickness: 9.0mm*), Wood Plastic Composite (WPC) Flooring with Painting Bevel (*Maximum thickness: 12.0mm*), Light Stone Plastic Composite/LSPC (*Maximum thickness: 10mm*), Light Stone Plastic Composite/LSPC with IXPE Foam (*Maximum thickness: 12mm*)